



OFFENSETM

Patented, Fast Acting, No Rinse Stripper

$\mathbf{OFFENSE}^{\text{TM}}\,\mathbf{quickly}\,\,\mathbf{penetrates}\,\,\mathbf{through}\,\,\mathbf{floor}\,\,\mathbf{finish}$

buildup and suspends the stripped finish for rinse free removal. Low foam and low odor. Safe on most resilient and non-resilient floors that include mineral surfaces, terrazzo, concrete, vinyl, vinyl composition, asphalt, rubber, terrazzo, brick and quarry tile. Do not use on linoleum or tile that are in poor condition.

NO RINSE OR NEUTRALIZING

Rinsing is not required. Pick up the dissolved finish completely with a wet vac, mop or autoscrubber.

MACHINE SCRUBBING NOT REQUIRED

The powerful solvent action of OFFENSETM dissolves finish buildup using only mop agitation.

SAFER TO USE

Works with cool water for increased worker safety.

TIME SAVER

OFFENSETM will reduce the time and labor required to strip floors by 40% as compared to current, conventional strippers.



| INGREDIENT | CAS# |
|--|------------|
| SOFT WATER | 7732-18-5 |
| ETHYLENE GLYCOL PHENYL ETHER | 122-99-6 |
| 2-AMINOETHANOL | 141-43-5 |
| BUTOXYETHANOL | 111-76-2 |
| SODIUM METASILICATE | 6834-92-0 |
| SODIUM 1-OCTANE SULFONATE | 5324-84-5 |
| SODIUM XYLENE SULFONATE | 1300-72-7 |
| ISOPROPYL ALCOHOL | 67-63-0 |
| TETRASODIUM EDTA | 64-02-8 |
| POLYETHOXYLATED METHYLOCTADECYLAMMONIUM METHYL SULFATE | 38096-68-3 |
| PARTIALLY FLUORONATED ALCOHOL | 65545-80-4 |

DIRECTIONS FOR USE

MOP ON - MOP OFF

- 1. **MIX** Dilute at 21 ounces per gallon (1:6 ratio) of cool water for normal buildup or 32 ounces per gallon (1:4 ratio) of cool water for extreme build up.
- 2. **MOP** the diluted solution of OFFENSE™ onto the floor. Let stand for 4-5 minutes, then agitate with the same mop. Do not allow solution to dry.
- 3. **REMOVE** the remaining solution off the floor using a mop or wet vacuum. For best results use a rotary machine and black pad. Do not let solution dry.
- 4. **REPEAT** steps two and three if any finish remains on floor. Rinsing may be required for dilutions stronger than 1:4.

SPECIAL PRECAUTIONS

Use caution as floors become very slippery. Must be diluted. Not for use on wood or painted surfaces. Not for use on linoleum or rubber floors or daily maintenance of resilient floors. Before use on asphalt tile, test a small hidden area for any color change.

PRODUCT SPECIFICATIONS

| pH (concentrate) | 13.0 ± 0.4 |
|----------------------|----------------------------|
| Color | Liquid, Clear to Colorless |
| Fragrance | Solvent |
| Freezing Point | 32°F |
| Solubility In Water. | Complete |
| Flash Point | None to Boiling |

PRODUCT AVAILABILITY

| F218022 | 4/1 Gallon |
|---------|-------------------|
| F218026 | 1/5 Gallon Pail |
| F218038 | 1/55 Gallon Drum |
| | (Special Order) |
| F218008 | 1/275 Gallon Tote |
| | (Special Order) |



One Fuller Way, Great Bend, KS 67530

800-848-4901 24-Hour Emergency 800.424.9300

fullerindustriesinc.com